






German standard wall mounting enclosure equipped with bipolar terminal blocks and two interchangeable flanges (1 flange with knock-out elements and 1 flange with quick entry cable glands).

|                                     |                    |                                     |                                                 |
|-------------------------------------|--------------------|-------------------------------------|-------------------------------------------------|
| Insulation class                    | II                 | Colour                              | Grey RAL 7035                                   |
| Outer dim. LxHxD (mm)               | 298x420x140        | IP degree                           | IP65                                            |
| Installation                        | Wall mounting      | Mechanical resistance               | IK07                                            |
| Door colour                         | Smoked Transparent | Terminal block N (mm <sup>2</sup> ) | (3x25)+(10x10)                                  |
| Terminal block T (mm <sup>2</sup> ) | (3x25)+(10x10)     | No. of modules EN 50022             | 24 (12X2)                                       |
| Glow Wire Test                      | 750 °C             | Standard                            | IEC EN 60670-1; IEC EN 60670-24; DIN VDE 0603-1 |
| Operating temperature               | -25 +60 °C         | Thermo-pressure with ball           | 70 °C                                           |
| Pole 1 (mm <sup>2</sup> )           | N (3x35) + (10x10) | Pole 2 (mm <sup>2</sup> )           | E (3x35) + (10x10)                              |

### DIMENSIONAL



| 1   | 2   | 3   | 4   |
|-----|-----|-----|-----|
| M16 | M20 | M25 | M32 |

|     | Codice                 | A   | B   | C   | D  | E  | F  | G     | H     | I   | P   | Q  | R  | S | T | U | V | W | X   | Y   | Z |
|-----|------------------------|-----|-----|-----|----|----|----|-------|-------|-----|-----|----|----|---|---|---|---|---|-----|-----|---|
| 12M | CW 40 113<br>CW 40 123 | 278 |     |     |    |    |    | 126.5 | 151.5 | /   |     |    |    |   |   |   |   |   |     | 161 |   |
| 24M | CW 40 114<br>CW 40 124 | 438 | 298 | 140 | 75 | 48 | 48 | 156.5 | 131.5 | 150 | 102 | 75 | 21 | 4 |   |   |   |   | 320 | 200 |   |
| 36M | CW 40 115<br>CW 40 125 | 598 |     |     |    |    |    | 156.5 | 131.5 | 150 |     |    |    |   |   |   |   |   | 494 |     |   |

### TECHNICAL SYMBOLOGY



II

IP

IP65

IK

IK07

GWT

750 °C

INSTALLATION



70 °C

### STANDARDS/APPROVALS



Reach  
Declaration

GEWISS S.p.A. Via A. Volta, 1

24069 Cenate Sotto - Bergamo - Italy

tel. +39 035 94 61 11 fax +39 035 94 69 09

Company subject to the management and coordination of Polfin S.p.A.

[www.gewiss.com](http://www.gewiss.com)

[sat@gewiss.com](mailto:sat@gewiss.com)

Last update 14/09/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice