

Product Data Sheet

coordination of Polim 2.9.4.  
Combsay anplect to the management and  
tel. +38 032 84 81 11 fax +38 032 84 88 08  
S7088 Censare 2010 - Bergamo - Italy  
GEWISS 2.9.4. Vols' t

last update 31.10.2028  
sai@gewiss.com  
www.gewiss.com

and could be changed without previous notice  
only as informative purposes  
data's measures' design and pictures are shown



Industrial-type socket-outlets conforming to IEC 309 Standard, with mechanical interlock consisting of a circuit breaker enabling the plug to be connected and disconnected only in the open position, and the switch to close only with the plug inserted. Wide range including models with rotary switch and fuseholder base, AUTOMATIKA with 6kA C characteristic miniature circuit breaker, and version with safety transformer. High application versatility thanks to the possibility of assembly in back-mounting and flush-mounting boxes, and boards of the 68 Q-DIN and Q-MC ranges.

|                        |                                      |                           |                                     |
|------------------------|--------------------------------------|---------------------------|-------------------------------------|
| Type                   | Vertical                             | Thermo-pressure with ball | 125 °C (IB socket) - 80 °C (bottom) |
| IP degree              | IP67                                 | No. of poles              | 3P+N+E                              |
| Mechanical resistance  | IK08                                 | Frequency                 | 50/60 Hz                            |
| Operating temperature  | -25 +40 °C                           | Protection                | MCB                                 |
| With back-mounting box | Yes                                  | Electrocod                | 2222                                |
| Glow wire test         | 850 °C (IB socket) - 650 °C (bottom) | Colour                    | Yellow                              |
| Circuit breaker        | MT 6 kA C characteristic             | Rated current (A)         | 16                                  |
| Reference h            | 4                                    | Rated voltage             | 100 - 130 V                         |

| BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS |               |                    |                    |                    |                    |               |               |                    |                    |           |
|------------------------------------------------|---------------|--------------------|--------------------|--------------------|--------------------|---------------|---------------|--------------------|--------------------|-----------|
| Saline solution                                | Acids         |                    | Bases              |                    | Solvents           |               |               |                    | Mineral oil        | UV rays   |
|                                                | Concentrated  | Diluted            | Concentrated       | Diluted            | Hexane             | Benzol        | Acetone       | Alcohol            |                    |           |
| Resistant                                      | Not resistant | Limited resistance | Limited resistance | Limited resistance | Limited resistance | Not resistant | Not resistant | Limited resistance | Limited resistance | Resistant |

DIMENSIONAL