



A product range comprising industrial-type socket-outlets conforming to IEC 60309 Standard, with rotary switch mechanical interlock for individual or group applications on modular bases. The robustness of the products and their resistance to the main chemical and atmospheric agents, together with the high IP66 degree of protection, mean they can be installed in tough environments with critical atmospheric, chemical and mechanical (accidental impact) conditions.

|                           |              |                             |                        |
|---------------------------|--------------|-----------------------------|------------------------|
| Type of fuse              | Ø 10.3x38 mm | Type                        | Vertical               |
| Thermo-pressure with ball | 80 °C        | Impact resistance at -20 °C | 20 J                   |
| IP degree                 | IP66         | No. of poles                | 3P+N+E                 |
| Mechanical resistance     | > IK10       | Frequency                   | 50/60 Hz               |
| Operating temperature     | -25 +40 °C   | Protection                  | Fuse-holder base (CBF) |
| With back-mounting box    | No           | Electrocod                  | 2222                   |
| Glow wire test            | 850 °C       | Colour                      | Blue                   |
| Rated current (A)         | 16           | Reference h                 | 9                      |
| Rated voltage             | 200 - 250 V  | Type of use                 | Heavy duty             |

#### BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

| Saline solution | Acids         |                    | Bases         |                    | Solvents  |           |                    |           | Mineral oil | UV rays   |
|-----------------|---------------|--------------------|---------------|--------------------|-----------|-----------|--------------------|-----------|-------------|-----------|
|                 | Concentrated  | Diluted            | Concentrated  | Diluted            | Hexane    | Benzol    | Acetone            | Alcohol   |             |           |
| Resistant       | Not resistant | Limited resistance | Not resistant | Limited resistance | Resistant | Resistant | Limited resistance | Resistant | Resistant   | Resistant |

#### DIMENSIONAL



#### TECHNICAL SYMBOLOGY



80 °C

**IP**

IP66

**IK**

> IK10

**GWT**

850 °C

-25 +40 °C

#### STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09  
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com  
sat@gewiss.com  
Last update 06/05/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice