

Product Data Sheet

GW68226N

68 Q-DIN Range



A complete system of IP65 boards for distributing energy in tertiary, commercial sector and building applications, available both empty and pre-wired, in accordance with the international standards EN 61439-3 and EN 61439-4. The distribution boards allow to house flush-mounting and interlocked socket-outlets up to 63 A and versions are available with 5, 10, 14 or 20 DIN modules and additional modules 14 and 20 DIN modules allow to increase modular space inside the boards. The switches can always be inspected, thanks to the wide transparent door with ergonomic handle and, thanks to the "hinged" screws of the front of the board, wiring and maintenance are easy. Q-DINs are ideal for fixed applications, surface-mounting or pole-mounting, and transportable applications, by handle and carrier. To ensure the best possible performance even in outdoor environments, prolonged exposure to the sun and bad weather, the boards are also UV resistant certified in compliance with EN 62208.

Type	Q-DIN 5 DBO	board type	Wired
Colour	Grey RAL 7035	Outer dim. LxHxD (mm)	105x340x120
Weight (kg)	1.5	Accordance with Standards	EN 61439-3 (DBO)
Characteristics	UV resistance (EN 62208)	IP degree	IP44
Mechanical resistance	IK09	Glow wire test	850 °C (active parts) - 650 °C (passive parts)
Thermo-pressure with ball	70 °C	Insulation class	II
Power supply	Terminal block	No. of poles	3P+N+E
Power supplyable (kW)	17.3	Mains switch	Not present
Circuits protection	MCB	No. socket outlets	2
Socket-outlet 2P+E 16A - IEC 309	1	Socket-outlet 3P+E 16A - IEC 309	1

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited resistance	Resistant	Resistant	Resistant	Limited resistance	Not resistant	Not resistant	Limited resistance	Limited resistance	Limited resistance

DIMENSIONAL



coordinatation of Polimix S.p.A.
Compassi subject to the management and
tel. +39 032 84 61 11 fax +39 032 84 60 00
Svizzera Centrale 20100 - Bergamo - Italy
GEWISS S.p.A. Via A. Volta, 1

last update 23/10/2020
sai@gewiss.com
www.gewiss.com

and could be changed without previous notice
only as informative purposes
Data, measures, designs and pictures are shown

OUTPUT PROTECTION	2x MTC
EMERGENCY PUSH-BUTTON	NO
POWER SUPPLY	Triphase

NOTE: the cell in grey identify 1 Socket-outlet.
Consult or download the electrical diagram from www.gewiss.com website.