Product Data Sheet
GW68232N
68 Q-DIN Range


A complete system of IP65 boards for distributing energy in tertiary, commercial sector and building applications, available both empty and pre-wired, in accordance with the international standards EN 61439-3 and EN 61439-4. The distribution boards allow to house flush-mounting and interlocked socket-outlets up to 63 A and versions are available with 5, 10, 14 or 20 DIN modules and additional modules 14 and 20 DIN modules allow to increase modular space inside the boards. The switches can always be inspected, thanks to the wide transparent door with ergonomic handle and, thanks to the "hinged" screws of the front of the board, wiring and maintenance are easy. Q-DINs are ideal for fixed applications, surface-mounting or pole-mounting, and transportable applications, by handle and carrier. To ensure the best possible performance even in outdoor environments, prolonged exposure to the sun and bad weather, the boards are also UV resistant certified in compilance with EN 62208.


Type	Q-DIN 10 DBO	board type	Wired
Colour	Grey RAL 7035	Outer dim. LxHxD (mm)	220x435x125
Weight (kg)	2.6	Accordance with Standards	EN 61439-3 (DBO)
Characteristics	UV resistance (EN 62208)	IP degree	IP65
Mechanical resistance	IK09	Glow wire test	850 °C (active parts) - 650 °C (passive parts)
Thermo-pressure with ball	70 °C	Insulation class	II
Power supply	Terminal block	No. of poles	2P+E
Power suppliable (kW)	5.8	Mains switch	Not present
Circuits protection	MCB	No. socket outlets	2
Socket-outlet 2P+E 16A - IB	2		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluited	Concentrated	Diluited	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited resistance	Resistant	Resistant	Resistant	Limited resistance	Not resistant	Not resistant	Limited resistance	Limited resistance	Limited resistance

DIMENSIONAL





Electrical Data								
GW68232N	16A - 2P+E	16A - 3P+E	16A - 3P+N+E	32A - 2P+E	32A - 3P+E	32A - 3P+N+E	63A - 3P+E	63A - 3P+N+E
SOCKET-OUTLET TYPE	2							
RATED CURRENT	25A							
RATED VOLTAGE	230V							
SHORT-CIRCUIT CURRENT (Icc)	6 kA							
MAIN SWITCH	-							
OUTPUT PROTECTION	2 x MTC							
EMERGENCY PUSH-BUTTON	NO							
POWER SUPPLY	Monophase							

NOTE: the cell in grey identify IB socket-outlet.
Consult or download the electrical diagram from www.Gewiss.com website.

TECHNICAL SYMBOLOGY

EN 61439-3 (DBO)

UV resistance (EN 62208)

IP65

IK09

850 °C (active parts) - 650 °C (passive parts)

70 °C

II

STANDARDS/APPROVALS

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 24/11/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice