
Product Data Sheet
GW70029
70 RT HP Range




70 RT HP is a complete offer of rotary isolator switches from 16 A to 160 A, available in boxes both in insulating material and aluminium, in control or emergency versions, compatible with the main applications for residential, tertiary and industrial contexts.
DC versions for photovoltaic applications are also available from 16 A to 40 A in insulating box.
The series is completed with versions for board from 16 A to 1000 A and for DIN rail fixing from 16 A to 63 A, which can be equipped with auxiliary contacts.
The devices have been designed to reduce wiring time, facilitate installation and guarantee the maximum safety and robustness even in the most demanding conditions.

ELECTRICAL CHARACTERISTICS	-	FUNCTIONAL CHARACTERISTICS	-
Rated operational current AC-15 (230 V) (A)	6	For isolator	100 A - 125 A - 160 A, 3P - 3P+N - 4P; 16 A - 25 A - 32 A - 40 A - 63 A - 100 A, 6P - 8P
Rated operational current AC-15 (380 V) (A)	3	Type of contact	1 NO + 1 NC

DIMENSIONAL





STANDARDS/APPROVALS

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 18/11/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice