

Product Data Sheet

GW70488P

70 RT HP Range



70 RT HP is a complete offer of rotary isolator switches from 16 A to 160 A, available in boxes both in insulating material and aluminium, in control or emergency versions, compatible with the main applications for residential, tertiary and industrial contexts.

DC versions for photovoltaic applications are also available from 16 A to 40 A in insulating box.

The series is completed with versions for board from 16 A to 1000 A and for DIN rail fixing from 16 A to 63 A, which can be equipped with auxiliary contacts.

The devices have been designed to reduce wiring time, facilitate installation and guarantee the maximum safety and robustness even in the most demanding conditions.


ELECTRICAL CHARACTERISTICS

	Rotary isolator	Version	Enclosed
Circuit breaker	25	Material	Insulating
Rated current (A)	4P	Type	For emergency
No. of poles	690	Knob colour	Red
Rated insulation voltage U_i (Vac)	25	Lockable	YES (max. 3 locks in OFF)
Rated operational current AC-21A (415 V) (A)	25	IP degree	IP66/IP67/IP69
Rated operational current AC-22A (415 V) (A)	25	Mechanical resistance	IK08
Rated operational current AC-23A (415 V) (A)	10	Protection against indirect contact	Double insulation
Conditional short circuit current I_{cc} (415 V) (kA)	1-10 mm ²	Operating temperature	-25 +60 °C
Cable section	-	Cable entries on top	2 x M20/M25 knock-outs
ACCESSORIES	-	Cable entries on bottom	2 x M20/M25 knock-outs
Type of accessory	Max. 2 auxiliary contacts (1 per side)		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Limited resistance	Resistant	Not resistant	Limited resistance	Limited resistance	Not resistant	Not resistant	Limited resistance	Resistant	Resistant

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IK

IP66/IP67/IP69

IK08

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and
coordination of Polfin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 23/09/2026

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice