





| Description                                                    | RESIDUAL CURRENT DEVICE |
|----------------------------------------------------------------|-------------------------|
| Code                                                           | BD                      |
| No. of poles                                                   | 2P                      |
| No. modules                                                    | 2                       |
| Rated current                                                  | 25 A                    |
| Rated residual operating current                               | 300 mA                  |
| Type                                                           | A                       |
| Rated voltage (IEC/EN 61009-1 app. G, IEC/EN 61009-2-1 app. G) | 230 V                   |

|                         |                                                |                                        |               |
|-------------------------|------------------------------------------------|----------------------------------------|---------------|
| Standard                | IEC/EN 61009-1 app. G, IEC/EN 61009-2-1 app. G | Rated frequency (Hz)                   | 50/60 Hz      |
| Insulation voltage (Ui) | 500 V                                          | Rated impulse withstand voltage (Uimp) | 4 kV          |
| Overvoltage category    | III                                            | Level of immunity (8/20 µs)            | 250 A         |
| Section rigid cable     | Max 35 mm²                                     | Section flexible cable                 | Max 35 mm²    |
| Operating temperature   | -25 +40 °C                                     | Storage temperature                    | -40°C ÷ +70°C |
| Rated tightening torque | 2 Nm                                           | Assembly position                      | Any           |

### DIMENSIONAL



### WIRING DIAGRAM



### STANDARDS/APPROVALS

