# Product Data Sheet

## GW94548


90 RCD Range




| | |
|---|---|
| Description | RESIDUAL CURRENT DEVICE |
| Code | BD |
| No. of poles | 3P |
| No. modules | 3.5 |
| Rated current | 63 A |
| Rated residual operating current | 300 mA |
| Type | A |
| Rated voltage (IEC/EN 61009-1 app. G, IEC/EN 61009-2-1 app. G) | 400 V |

| | | | |
|---|---|---|---|
| Standard | IEC/EN 61009-1 app. G, IEC/EN 61009-2-1 app. G | Insulation voltage (Ui) | 500 V |
| Rated impulse withstand voltage (Uimp) | 4 kV | Overvoltage category | III |
| Level of immunity (8/20 µs) | 250 A | Section rigid cable | Max 35 mm² |
| Section flexible cable | Max 35 mm² | Operating temperature | -25 +40 °C |
| Stocking temperature | -40°C ÷ +70°C | Rated tightening torque | 2 Nm |
| Assembly position | Any | | |

## DIMENSIONAL




## WIRING DIAGRAM




## STANDARDS/APPROVALS

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 03/11/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice