




Description Interruttore automatico scatolato
 Code MSX 160c
 No. of poles 3P+N
 Rated current 25 A
 Release Electromechanic

ELECTRICAL CHARACTERISTICS		MECHANICAL CHARACTERISTICS	
Standard	IEC/EN 60947-2	Execution	Fixed
Use category	A	DIN rail mounting	Yes, by means of accessory
Rated frequency (Hz)	50 / 60	Can be equipped with motor operator	No
Rated operating voltage (Ue)	525 V ac - 250 V dc	Compatible interlock	-
Rated impulse withstand voltage (Uimp)	8 kV	Terminals supplied	Front for FW cables
Overtoltage category	IV	Assembly position	Any
Insulation voltage (Ui)	690 V	Upline/downline power supply	Yes
Thermal regulation	0,63 - 0,8 - 1 x In	Electrical life (415Vac)	14.000 cycles
Magnetic regulation	Fisso - 600A	Mechanical life	20.000 cycles
Neutral protection	Not protected	Operating temperature	-5°C +65°C
Total power loss	18.4 W	Stocking temperature	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Weight (kg)	1
Rated short-time withstand current for 0,3s (Icw)	-	Width	100 mm
I _{dn} regulation	-	Height	130 mm
DT regulation	-	Depth	68 mm
SERVICE BREAKING CAPACITY (ICU)		RATED BREAKING CAPACITY (ICS)	
220/240Vac	25 kA	220/240Vac	13 kA
400/415Vac	16 kA	400/415Vac	8 kA
440Vac	10 kA	440Vac	5 kA
525Vac	6 kA	525Vac	3 kA
690Vac	-	690Vac	-
250Vdc	13 kA	250Vdc	7 kA

DIMENSIONAL





Product Data Sheet

GWD9011

MSX

STANDARDS/APPROVALS

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and
coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 29/04/2026

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice