




Description Interruttore automatico scatolato
 Code MSX 160c
 No. of poles 3P
 Rated current 40 A
 Release Electromechanic

| ELECTRICAL CHARACTERISTICS | | MECHANICAL CHARACTERISTICS | |
|---|---------------------|-------------------------------------|----------------------------|
| Standard | IEC/EN 60947-2 | Execution | Fixed |
| Use category | A | DIN rail mounting | Yes, by means of accessory |
| Rated frequency (Hz) | 50 / 60 | Can be equipped with motor operator | No |
| Rated operating voltage (Ue) | 525 V ac - 250 V dc | Compatible interlock | - |
| Rated impulse withstand voltage (Uimp) | 8 kV | Terminals supplied | Front for FW cables |
| Overtoltage category | IV | Assembly position | Any |
| Insulation voltage (Ui) | 690 V | Upline/downline power supply | Yes |
| Thermal regulation | 0,63 - 0,8 - 1 x In | Electrical life (415Vac) | 14.000 cycles |
| Magnetic regulation | Fisso - 600A | Mechanical life | 20.000 cycles |
| Neutral protection | - | Operating temperature | -5°C +65°C |
| Total power loss | 11.1 W | Stocking temperature | -20° +65° |
| Rated short-circuit current making capacity (Icm) | - | Weight (kg) | 0.8 |
| Rated short-time withstand current for 0,3s (Icw) | - | Width | 75 mm |
| I _{dn} regulation | - | Height | 130 mm |
| DT regulation | - | Depth | 68 mm |
| SERVICE BREAKING CAPACITY (ICU) | | RATED BREAKING CAPACITY (ICS) | |
| 220/240Vac | 35 kA | 220/240Vac | 18 kA |
| 400/415Vac | 25 kA | 400/415Vac | 13 kA |
| 440Vac | 15 kA | 440Vac | 7,5 kA |
| 525Vac | 7,5 kA | 525Vac | 4 kA |
| 690Vac | - | 690Vac | - |
| 250Vdc | 20 kA | 250Vdc | 10 kA |

DIMENSIONAL





Product Data Sheet

GWD9042

MSX

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and
coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 29/04/2026

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice