Product Data Sheet

GWD9263

MSX




Description	Interruttore automatico scatolato
Code	MSXD 125
No. of poles	3P
Rated current	50 A
Release	Electromechanic

ELECTRICAL CHARACTERISTICS	-
Standard	IEC/EN 60947-2
Use category	A
Rated frequency (Hz)	50 / 60
Rated operating voltage (Ue)	525 V ac
Rated impulse withstand voltage (Uimp)	8 kV
Overvoltage category	IV
Insulation voltage (Ui)	525 V
Thermal regulation	0.63 - 0.8 - 1 x In
Magnetic regulation	Fixed - 500 A
Neutral protection	-
Total power loss	14.94 W
Rated short-circuit current making capacity (Icm)	-
Rated short-time withstand current for 0,3s (Icw)	-
Idn regulation	0.03 - 0.1 - 0.3 - 0.5 - 1 - 3 A
DT regulation	0 - 60 - 200 - 400 - 700 ms
SERVICE BREAKING CAPACITY (ICU)	-
220/240Vac	50 kA
400/415Vac	36 kA
440Vac	25 kA
525Vac	22 kA
690Vac	-
250Vdc	-

MECHANICAL CHARACTERISTICS	-
Execution	Fixed
DIN rail mounting	Yes, by means of accessory
Can be equipped with motor operator	Yes
Compatible interlock	-
Terminals supplied	Front FC
Assembly position	Any
Upline/downline power supply	Yes
Electrical life (415Vac)	30.000 cycles
Mechanical life	30.000 cycles
Operating temperature	-5°C +65°C
Stocking temperature	-20° +65°
Weight (kg)	1.1
Width	90 mm
Height	155 mm
Depth	68 mm
RATED BREAKING CAPACITIY (ICS)	-
220/240Vac	50 kA
400/415Vac	36 / 30 kA
440Vac	25 kA
525Vac	22 kA
690Vac	-
250Vdc	-

DIMENSIONAL



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 31/10/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice

Product Data Sheet

GWD9263

MSX

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 31/10/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice