# Product Data Sheet

# GWD9367


MSX



| | |
|---|---|
| Description | Interruttore automatico scatolato |
| Code | MSX 400 |
| No. of poles | 4P |
| Rated current | 400 A |
| Release | Electromechanic |

| **ELECTRICAL CHARACTERISTICS** | - | **MECHANICAL CHARACTERISTICS** | - |
|---|---|---|---|
| Standard | IEC/EN 60947-2 | Execution | Fixed - Plug-in |
| Use category | A | DIN rail mounting | No |
| Rated frequency (Hz) | 50 / 60 | Can be equipped with motor operator | Yes |
| Rated operating voltage (Ue) | 690 V ac - 250 V dc | Compatible interlock | Lever – Cable |
| Rated impulse withstand voltage (Uimp) | 8 kV | Terminals supplied | Front FC |
| Overvoltage category | IV | Assembly position | Any |
| Insulation voltage (Ui) | 800 V | Upline/downline power supply | Yes |
| Thermal regulation | 0.63 - 0.8 - 1 x In | Electrical life (415Vac) | 4.500 cycles |
| Magnetic regulation | 6 - 8 - 10 - 12 x In | Mechanical life | 15.000 cycles |
| Neutral protection | 100% x Ir | Operating temperature | -5°C +65°C |
| Total power loss | 89.6 W | Stocking temperature | -20° +65° |
| Rated short-circuit current making capacity (Icm) | - | Weight (kg) | 5.6 |
| Rated short-time withstand current for 0,3s (Icw) | - | Width | 185 mm |
| Idn regulation | - | Height | 260 mm |
| DT regulation | - | Depth | 103 mm |
| **SERVICE BREAKING CAPACITY (ICU)** | - | **RATED BREAKING CAPACITIY (ICS)** | - |
| 220/240Vac | 85 kA | 220/240Vac | 85 kA |
| 400/415Vac | 50 kA | 400/415Vac | 50 kA |
| 440Vac | 45 kA | 440Vac | 45 kA |
| 525Vac | 30 kA | 525Vac | 30 kA |
| 690Vac | 20 kA | 690Vac | 15 kA |
| 250Vdc | 40 kA | 250Vdc | 40 kA |

## DIMENSIONAL




GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 31/10/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice

Product Data Sheet

# GWD9367

MSX

## STANDARDS/APPROVALS




GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 31/10/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice