


On request




Smart [3] is a watertight fixture IP66/69 with Flip Type LED without wire bonding, available in 3000K,4000K,5700K, with CRI ≥80. IK08 body in RAL7035 colored self-exhausting polycarbonate, for industrial applications and ideal for production areas, warehouses, logistics areas and design to replace fluorescent devices and lowbay up to 6.500lm. Available in sizes 800, 1200, 1600mm, powers from 18W to 58W, flux range from 1.700lm to 6.500lm, with integrated Power On/Off or DALI and 2 different optical solutions UV-stabilized self-extinguishing polycarbonate, in opal or transparent finish. The version with passing wiring has mechanical and electrical connection components prewired, with up to 25 fixtures installed in a continuous row. The device can be hung or wall mounted and is available a GW bracket accessories with a tilt of 30° or 45° on the vertical axis. Available also with an emergency kit version.

panoları	İç	Seri	SMART [3]
Tip	Tek başına	IP derecesi	IP66/IP69
Direnç dayanıklı	IK08	Yalıtım sınıfı	II
Akkor Tel Deneyi:	850 °C	uzunluğu	1600 mm
Yüzey sıcaklığı azaltılmış cihaz	Uyumlu	Ekran tipi	Opal
Çalıştırma sıcaklığı	-30 +50 °C	Ağırlık (kg)	2.5
Voltaj	220/240 V - 50/60 Hz - tek başına	Lamba	LED
Sürücü tipi	Constant Current Driver Led	Sistem gücü	26 W
Işık kaynağı tipi	LED - değiştirilemez	Renk sıcaklığı	3000 K (CRI>80)
Entegre LED'lerin etkinlik sınıfı	A + A++	Nominal flux (lm)	3500
Lümen çıkışı (lm)	2800	LED Life Time (L80B50)	100000 h
LED Life Time (L90B50)	50000 h	LED LifeTime (L80B20)	85000 h
Failure rate apparecchio (35.000h, Tq=35° C)	<2,5%	Failure rate apparecchio (50.000h, Tq=25° C)	<2,5%
Garanti	5 yıl	Overvoltage resistance	Common mode: 2KV; Differential mode: 1KV
Elektrokod	2434		

### DIMENSIONAL



### PHOTOMETRIC DISTRIBUTION



### TECHNICAL SYMBOLOGY



IP

IP66/IP69

IK

IK08



GWT

850 °C



CONSTANT  
CURRENT  
DRIVER



### STANDARDS/APPROVALS

