

German standard flush mounting enclosure for brickwork walls equipped with bipolar terminal blocks.



Insulation class	II	Colour	RAL 9003 White
Outer dim. LxHxD (mm)	338x335x92,5	IP degree	IP40
Installation	Flush mounting enclosures	Dispersible power (W)	28
Mechanical resistance	IK07	Door colour	Blank
Terminal block N (mm <sup>2</sup> )	(1x25)+(3x16)+(14x10)	Terminal block T (mm <sup>2</sup> )	(1x25)+(3x16)+(14x10)
No. of modules EN 50022	12+2	Glow Wire Test	750 °C
For walls	Masonry	Standard	IEC EN 60670-1; IEC EN 60670-24; DIN VDE 0603-1; DIN 43871
Operating temperature	-15 ÷ +60°C	Electrocod	0310
Thermo-pressure with ball	70 °C	Pole 1 (mm <sup>2</sup> )	N (1x25)+(3x16)+(14x10)
Pole 2 (mm <sup>2</sup> )	E (1x25)+(3x16)+(14x10)		

#### BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Not resistant	Limited resistance	Limited resistance	Not resistant	Limited resistance	Not resistant	Not resistant	Limited resistance	Limited resistance	Resistant

#### DIMENSIONAL

#### TECHNICAL SYMBOLOGY



II

IP


IP40

IK

IK07

GWT

750 °C



-15 ÷ +60°C



70 °C

#### STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 11/05/2021

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice