# Product Data Sheet
# GW68596F

68 ACS Range

The distribution board for construction sites type Q-BOX are designed to withstand the effects of wear, impact and the stress caused by atmosph. They come in pre-wired versions fitted with interlocked socket-outlets (with or without a fuse-holder) up to 63A, or socket-outlets type IEC 309.. The wired versions are also equipped with accessories like the emergency push-button, lockable doors, stainless steel tear-proof cable-fastening hooks, and built-in transportation handles on the upper part of the board. To ensure the best possible positioning on the construction site, 68 Q-BOX ACS boards can be surface-mounted, floor-mounted or fitted on poles.

| | | | |
|---|---|---|---|
| Type | Q-BOX 6 ACS | board type | Wired |
| Colour | Light blue | Outer dim. LxHxD (mm) | 914x821x400 |
| Weight (kg) | 30 | Accordance with Standards | EN 61439-4 (ACS) |
| Characteristics | UV resistance (EN 62208) | IP degree | IP55 |
| Mechanical resistance | IK10 | Glow wire test | 650 °C |
| Thermo-pressure with ball | 70 °C | Insulation class | II |
| Power supply | Fixed plug | No. of poles | 3P+N+E |
| Power suppliable (kW) | 17 | Mains switch | RCBO 32A 4P 6 kA 0,03A - AC type |
| Circuits protection | Fuse | No. socket outlets | 6 |
| Socket-outlet 2P+E 16A - IB | 3 | Socket-outlet 3P+E 16A - IB | 2 |
| Socket-outlet 3P+N+E 16A - IB | 1 | Emergency push-button | Yes |
| Electrocod | 139 | | |

## BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

| Saline solution | Acids | | Bases | | Solvents | | | | Mineral oil | UV rays |
|---|---|---|---|---|---|---|---|---|---|---|
| | Concentrated | Diluited | Concentrated | Diluited | Hexane | Benzol | Acetone | Ethyl alcohol | | |
| Resistant | Limited resistance | Resistant | Limited resistance | Resistant | Limited resistance | Limited resistance | Limited resistance | Resistant | Limited resistance | Resistant |

## DIMENSIONAL




## TECHNICAL SYMBOLOGY

EN 61439-4 (ACS)

UV resistance (EN 62208)

IP55

IK10

650 °C

70 °C

II

## STANDARDS/APPROVALS

GEWISS S.p.A. Via Domenico Bosatelli 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 24/04/2024

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice