



A complete, versatile system of modular containers, perfectly integrable in the SYSTEM domestic range and able to meet the high protection installation requirements of the residential, commercial and industrial sectors. The 27 COMBI range is available both in the IP40 version and in watertight versions with IP55, IP65 and IP66 degree of protection, recommended for all outdoor applications which are subjected to extreme atmospheric conditions.

Colour	Grey RAL 7035	Door type	Rigid
Door colour	Smoked Transparent	No. knockout holes Ø23	18 on sides / 2 on the bottom
Type of knockout holes	Removable with tool	IP degree	IP40
Insulation class	II	Mechanical resistance	IK07
Configuration	Module 4 x 4	Compartment pre-arrangement	2
Type of enclosure	GP	No. SYSTEM modules	16
No. DIN modules	8	Characteristics	Halogen free
Lid screws	Stainless steel	Torque screws tightening	0.8 Newton/meter
Outer dim. LxHxD (mm)	429x132x95	Dispersible power (W)	18
Rated voltage	400V ac	Rated current (In)	32 A
Insulation voltage	750 V	Glow Wire Test	650 °C
Thermo-pressure with ball	70 °C	Standard	EN 60670-1 - EN 60670-24
Installation temperature	-25 +60 °C	Electrocod	0212

DIMENSIONAL

TECHNICAL SYMBOLOGY



Removable with tool

IP

IP40



II

IK

IK07



Halogen free

GWT

650 °C



70 °C

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 18/04/2021

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice