


Wide range of control devices, sockets for power supply (conforming to national and international standards), signal pick-up, climate control, comfort management, technical alarm signalling, and emergency lighting management. Chorus modular devices are available in five colours, glossy white, satin white, natural beige, satin black and painted titanium and in different sizes, 1/2, 1, 2 and 3 modules. Thanks to the mounting supports for rectangular, square and round boxes, endless combinations can be created with the Chorus range of plates.

| | | | |
|---|--------------------------------|---|-------------------------------|
| Category | One-way switch | Button key | With replaceable neutral lens |
| Colour | Glossy Titanium | Description | 1P - 16AX illuminable |
| Voltage | 250 V ac | Standard | EN 60669-1 |
| Resistance at test voltage | 2000 V at 50 Hz for 1 minute | Rated power of 230V LED lamps | 200 W |
| Insulation resistance | > 5 MOhm | Wiring terminals | With screw |
| Prolonged operation switch (no.of position changes) | 40.000 at In 250 V ac cosØ=0,6 | Thermo-pressure with ball | 125 °C |
| Glow Wire Test | 850 °C | Terminal grip on cable traction | > 50 N |
| Terminal tightening capacity stranded cables (mm2) | min. 0,75 - max. 2x4 | Terminal tightening capacity solid cables (mm2) | min. 0,5 - max. 2x2,5 |
| No. modules | 3 | Material | Technopolymer |
| Electrocod | 0130 | | |

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

