Product Data Sheet

GWS2992

ELIA AL

Kit for emergency use equipped with Ni-Cd battery with 3h autonomy after 24h of recharge. Equipped with a test button to check the status of the battery, it must be positioned on the luminaire. Warranty 2 years, battery and inverter excluded. Compatible with the following ranges: ELIA AL, ELIA DL and ELIA PL. NOT COMPATIBLE with the ELIA PL IP65 range.

Description	Emergency kit 3h	Series	ELIA AL, ELIA DL, ELIA PL, ELIA PL BACKLIT, VISIO [16] - NOT COMPATIBLE WITH ELIA PL IP65
Type	Emergency kit	Version	Permanent 3 h
Power	4 W	Application	Internal
Operating temperature	0 +25 °C	IP degree	IP20
Mechanical resistance	IK03	Autonomy	3 h
Fixing	Device edge	Insulation class	II
Power supply batteries	Replaceable	Voltage	220-240 V - 50/60 Hz
Charging time	24 h	Weight (kg)	0.8
Electrocod	2419		

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION

TECHNICAL SYMBOLOGY

IP	IK
IP20	IK03

STANDARDS/APPROVALS

Data, measures, designs and pictures are for information purpose only, last update 25/04/2024. They can be changed at any moment, therefore it is always ecommended to read the last updated version published on the website www.gewiss.com.Lumen output and system power are subject to a tolerance of +/- 10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C. Terms of warranty at https://www.gewiss.com/it/en/company/landingpage/led-warranty. - 1 of 1