


Modular recessed luminaire 300x1200 mm. Extruded aluminum frame with thermoplastic oven paint. Plastic diffuser with "fulllight" emission. MID Power LED Light Source.

|                    |                             |                                     |                           |
|--------------------|-----------------------------|-------------------------------------|---------------------------|
| Application        | Internal                    | Installation                        | Flush mounting enclosures |
| Dimensions (mm)    | 300 x 1200                  | Mechanical resistance               | IK04                      |
| Voltage            | 220/240 V - 50/60 Hz - DALI | System power                        | 40 W                      |
| Weight (kg)        | 3.4                         | Lamp                                | LED                       |
| Colour             | White                       | Lumen output (lm)                   | 3630                      |
| IP degree          | IP20 - IP40                 | Insulation class                    | II                        |
| Driver type        | Driver Led                  | Operating temperature               | -25 +40 °C                |
| UGR                | <=19                        | Warranty                            | 5 years                   |
| Colour temperature | 4000 K (CRI>80)             | Efficiency class of integrated LEDs | A ÷ A++                   |
| Electrocod         | 2419                        | LED Life Time (L70B30)              | 50000 h                   |

### DIMENSIONAL



### PHOTOMETRIC DISTRIBUTION



### TECHNICAL SYMBOLOGY



IK  
IK04



IP  
IP20 - IP40



### STANDARDS/APPROVALS

