Product Data Sheet

GW40610

40 CDi-serie

The range of IP40 protected flush mounting enclosures offers sizes from 2 to 72 modules, available with a smoked transparent door (particularly suitable for the commercial and industrial sector) or a blank door (ideal for domotic application). They can be equipped with bipolar and unipolar terminal blocks, 80 A and 125 A, with screw wiring; they allow to create simple and neat wiring reducing the set-up time of the enclosure.

Isolatie-klasse	II (conform de norm IEC 61140)	Kleur	Wit RAL 9016
Buitenafm. LxHxD (mm)	465x680x95	IP-graad	IP40
Installatie	Voor bakstenen muur	Vermogen-verspreiding (W)	62
Stoot-bestendigheid	IK08	Nominale spanning	400 V
Deur kleur	Transparant fumé	Aantal modules EN 50022	54 (18x3)
Nominale stroom	125 A	Gloeidraadproef	650 °C
Bedrijfstemperatuur	-15 ÷ +60°C	Type materiaal	Halogeenvrij conform EN 60754-2
Electrocod	0311	Thermospanning met kogel	70 °C
Standaard	EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49	Isolatie-spanning	750 V
Max. installeerbare klemmenblokken	3 x 18 modules		

DIMENSIONAL



		A	B	C	N	D	E	F	G	H	P	D	'E	'F	'I	L	M
24M	GW 40 606 GW 40 886	420	330	16	101	75	48	17	148	122	150	-	-	-	380	290	85
36M	GW 40 609 GW 40 889	505	465	16	101	75	48	17	175	155	175	-	-	-	465	427	85
54M	GW 40 610 GW 40 890	680	465	25	120	75	48	37	175	155	175	101	74	11	630	415	95
72M	GW 40 611 GW 40 891	880	465	25	120	75	48	37	175	155	175	101	74	11	805	415	95

TECHNICAL SYMBOLOGY

EN 61140
II (conform de norm IEC 61140)

IP
IP40

IK
IK08

GWT
650 °C

-15 ÷ +60°C

HF HALOGEN FREE
Halogeenvrij conform EN 60754-2

70 °C

STANDARDS/APPROVALS

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 23/04/2024

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice