





The IP40 protected decorative enclosures are available in sizes from 8 to 72M. They provide superior aesthetic integration. They are available with smoked transparent doors or with blank doors that can be equipped with safety lock, characterized by the "PUSH" opening and closing. They can be equipped with bipolar and unipolar terminal blocks, 80 A and 125 A, with screw wiring; they allow to create simple and neat wiring reducing the set-up time of the enclosure.

Classe isolamento	II (Norma IEC 61140)	Cor	Branco RAL 9016
Dim. externas BxHxP (mm)	400x550x130	Grau de protecção	IP40
Potência dissipável (W)	63	Resistên. golpes	IK08
Tensão nominal	400 V	Cor porta	Transparente fumado
N. mód. EN 50022	54 (18x3)	Corrente nominal	125 A
Glow Wire Test	650 °C	Temperatura de instalação	-25 +60 °C
Tipo de material	Livre halogéneos segundo EN 60754-2	Código Electrocod	0321
Termopressão com esfera	70 °C	Acessórios para a restauração do isolamento	Screwcaps (GW44623) or fixing brackets in resin (GW44621)
Norma	EN 60670-1, IEC60670-24	Tensão de isolamento	750 V
Nº mais blocos de terminais instaláveis	2 x 18 módulos		



DIMENSIONAL

TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

