




The distribution board for construction sites type Q-BOX are designed to withstand the effects of wear, impact and the stress caused by atmosph. They come in pre-wired versions fitted with interlocked socket-outlets (with or without a fuse-holder) up to 63A, or socket-outlets type IEC 309.. The wired versions are also equipped with accessories like the emergency push-button, lockable doors, stainless steel tear-proof cable-fastening hooks, and built-in transportation handles on the upper part of the board. To ensure the best possible positioning on the construction site, 68 Q-BOX ACS boards can be surface-mounted, floor-mounted or fitted on poles.

Tipologia	Q-BOX 4 ACS	board type	Cablagem
Cor	Azul claro	Dim. externas BxHxP (mm)	636x821x400
Peso (kg)	21	Conformidade normativa	EN 61439-4 (ASC)
Características	Resistência UV (EN 62208)	Grau de protecção	IP55
Resistên. golpes	IK10	Teste de fio incandescente	650 °C
Termopressão com esfera	70 °C	Classe isolação	II
Alimentação	Ficha fixa	N. pólos	3P+N+T
Potência distribuível (kW)	17	Disjuntores geral	RCBO 32A 4P 6 kA 0,03A - AC type
interruptor magnéto-termico	RCCB 40A 4P 0,03A - AC type	Circuits protection	MCB
N. tomadas	4	Tomada 2P+T 16A - IB	3
Tomada 3P+T 16A - IB	1	Emergency push-button	Si
Código Electrocod	139		



DIMENSIONAL



TECHNICAL SYMBOLOGY



EN 61439-4 (ASC)



Resistência UV (EN 62208)

IP

IP55

IK

IK10

GWT

650 °C



70 °C



II

STANDARDS/APPROVALS

