

### ESALITE PL



Industrial LED lighting fixture made of die-cast EN AB 46100 aluminium with polyester powder coating. Correct illumination is provided by an optical system composed of different versions of lenses and sealed by an extra-clear tempered glass of 4mm. Silicone gaskets, Goretex breathing and anti-condensation device, waterproof connector for 1.5 mm<sup>2</sup> cables and stainless steel external screws. Integrated suspension fixing system thanks to a ring made directly in the die-cast aluminium. The die-cast aluminium structure guarantees optimal performance conditions both at Ta25° and Ta50° thanks to specific thermal sizing tests. The correct heat dispersion inside ESALITE is guaranteed by the special passive heat sink with a very low copper content that offers high qualitative and quantitative performances.

#### GENERAL INFORMATION

Context	Lighting for parks and green areas
Luminaire	LED luminaire with mid and high lumen power
Aplicação	Interior/Exterior
Unique digital code (Datamatrix)	Datamatrix
Cor	Cinza RAL 9006
Tipo de fonte luminosa	LED - Não substituível
Potência de sistema	52 W
LED Lifetime	L90B10 (Tq 25°) 100000 h; L90B10 (Tq 50°) 55000 h
Peso (kg)	3.8

#### OPTIC AND ILLUMINATING FEATURES

Óptica	Média 60°
Unified Glare Rating	UGR ≤ 28
Lúmen saída (lm)	5800
Efficiency (lm/W)	112
Temperatura de cor	4000 K
Color Rendering Index	CRI>80
Standard Deviation Colour Matching	SDCM = 3
Photobiological Risk Class	-
Norma	EN60598-1; EN60598-2-5; IEC 62778; IEC62471

Garantia	5 anos
Temperatura de armazenagem	-25°C ÷ +70°C / HR 10% ÷ 85%
Operating temperature	-25°C ÷ +50°C

#### ELETRICAL AND LIGHTING FEATURES

Tensão de alimentação	220-240 V
Frequência nominal (Hz)	50/60 Hz
Driver	Included
Driver failure rate	F10 = 100.000h Tq25°C/50.000h Tq50°C
Overvoltage protection	DM 6KV / CM 8KV
Control System	DALI

#### MATERIALS

Body	Injeção de alumínio
Vidro	Flat tempered glass 4mm
Optic	PMMA lens
Gasket	CNC deposited sealant
Locking Hook	-
External screw	Stainless steel
Colour	Polyester powder coated

#### INSTALLATION AND MAINTENANCE


Mouting and installation	Wall/ground
Tilt	With graduated support
Wiring	With watertight connector
Fixação	-

#### STANDARDS AND APPROVALS


Classificação	-
Aparelho com reduzida temperatura superficial	-
Certificação DIN 18032-3	No
IPEA	-
Classe isolamento	I
Grau de protecção	IP66
Resistên. golpes	IK08
Glow Wire Test	-

Optic Maintenance	Not available
LED Maintenance	Not available
Driver Box	Integrado
Superfície máxima exposta ao vento	0,07 m <sup>2</sup>

#### DIMENSIONAL



#### PHOTOMETRIC DISTRIBUTION



#### TECHNICAL SYMBOLOGY



IP  
IP66

IK  
IK08

GWT  
-

#### STANDARDS/APPROVALS

Data, measures, designs and pictures are for information purpose only, last update 09/05/2021. They can be changed at any moment, therefore it is always recommended to read the last updated version published on the website [www.gewiss.com](http://www.gewiss.com). Lumen output and system power are subject to a tolerance of +/- 10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C. Terms of warranty at <https://www.gewiss.com/it/en/company/landingpage/led-warranty>. - 1 of 2



ESALITE PL

