




The main supply boards for the construction site type 68 QP ACS and 68 CDK ACSK: installed immediately downstream from the energy meter, to protect the line from the delivery board to the main site distribution board. They are available in versions with power from 17 kW (32A) to 130 kW (250A), all fitted with an emergency push-button.

Tip	CDK ACS	board type	Kablolu
Renk	Gri RAL 7035	Dış boyut LxHxD (mm)	298x260x140
Ağırlık (kg)	4	Standartlarla uyum	EN 61439-4 (ASC)
Özellikler	UV rezistans (EN 62208)	IP derecesi	IP65
Direnç dayanıklı	IK09	Akkor Tel Deneyi	650 °C
Bilyeli termo sıcaklık	70 °C	Yalıtım sınıfı	II
Kutup adedi	4	beslenebilir (KW) güç (kW)	33
Ana anahtar	MCB 63A 4P 6kA	MCB'S MT main RCCB	MT + BD 63 A
Emergency push-button	Evet	Elektrokod	139



## DIMENSIONAL


## TECHNICAL SYMBOLOGY



**IP**  
IP65

**IK**  
IK09

**GWT**  
650 °C



## STANDARDS/APPROVALS

GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 18/11/2019

Data, measures, designs and pictures are shown only as informativ purposes, and could be changed without previous notice