Product Data Sheet

GW84205

68 ACS Serisi

Multifunctional floodlights in die-cast aluminium, painted with polyester powders, for portable applications on tubular support Optic in 99.85% polished and anodised aluminium Flat tempered glass 5mm thickness Anti-aging silicone gasket Suitable for use with halogen lamps Equipped with protective wire guard and cable type H07RN-F section 3x1,5mm² lenght 5m with plug IEC 309 2P+E 200-250V IP67

panoları	Dış	Kullanım tipi	Taşınabilir
IP derecesi	IP55	Direnç dayanıklı	IK10
Yalıtım sınıfı	I	Aydınlatılan nesneden minimum uzaklık	1.4 m
Ağırlık (kg)	4.8	Renk	Grafit grisi
Lamba akımı	4.3 A	Maks. lamba gücü	1000 W
Lamba tutucu	R7s	Lamba	HD
Uyumlu lambaların etkinlik sınıfı	C ÷ B	Optik	Simetrik optik - ULOR: 0%
Elektrokod	2424		

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY

IP IP55

IK IK10

1.4 m

STANDARDS/APPROVALS

CE

Data, measures, designs and pictures are for information purpose only, last update 19/04/2024. They can be changed at any moment, therefore it is always ecommended to read the last updated version published on the website www.gewiss.com.Lumen output and system power are subject to a tolerance of +/- 10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C. Terms of warranty at https://www.gewiss.com/it/en/company/landingpage/led-warranty. - 1 of 1