






Wide range of switches, energy sockets (compliant with national and international standards), data sockets, devices for the management of climate control, comfort, technical alarms signalling, emergency lighting. The Chorus modular devices are available in four colors, glossy white, satin black, painted titanium and glossy ivory and in different modularities, 1/2, 1, 2 and 3 modules. Thanks to the frame supports for rectangular, square and round boxes, the devices allow you to create endless combinations with the range of Chorus plates.

Kategori	Vavien	Tuř	Deęiřtirilebilir gstergeli
Renk	Titanyum	Tanım	1P - 16AX ışıklandırılabilir
Voltaj	250 V ac	Standart	EN 60669-1
Test voltajındaki rezistans	1 dak. için 2000 V a 50 Hz	Rated power of 230V LED lamps	200 W
Yalıtım direnci	> 5 MOhm	Kablolama terminalleri	Çabuk, yaylı
Uzatılmış kullanım (konum deęişiklikleri sayısı)	40.000, 250 V ac cosØ=0,6	Bilyeli termo sıcaklık	125 °C
Akkor Tel Deneyi:	850 °C	Kablo çekmede terminal tutuřu	> 50 N
Terminal sıkıřtırma kapasitesi esnek kablolar (mm2)	min. 0,75 - maks. 2x4	Terminal sıkıřtırma kapasitesi sert kablolar (mm2)	min. 0,5 - maks. 2x2,5
Chorus sayısı modüller	2	Elektrokod	0130
Elektrokod	0130		

DIMENSIONAL



TECHNICAL SYMBOLOGY

GWT

850 °C

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 19/06/2019

Data, measures, designs and pictures are shown only as informativ purposes, and could be changed without previous notice