



A complete system for the connection and distribution of LAN networks in the residential and tertiary sector. The range includes solutions for optical fibre, wall cabinets, floor-standing cabinets and products for copper wiring. The Data Center range includes all the products needed to create an optical fibre multi-service infrastructure for residential buildings, fully complying with all the indications of the new CEI 306-2 guide and Italian law 164/14.

Kategori	Bretella ottica	Cable colour	Beyaz
No. optical fibers	1	uzunluğu	40 m
Ø sheath	2 mm	For connectors	SC/APC - SC/APC
Sınıflandırma	G.657.A2 / B6_a2 Bend Insensitive	Ø core	9 µm
Ø cladding	125 µm	Strength member	Kevlar
Outer jacket	LSZH	Kablo	Loose - OS2
Tension	60 N	Crush	100 N/10cm
Minimum bend radius (Dynamic)	20x diametro cavo	Minimum bend radius (Static)	10x diametro cavo
Max attenuation (@1310 nm / @1550 nm)	0.35 / 0.2 dB/Km	Kullanım sıcaklığı	Da -20°C a +60°C

## DIMENSIONAL

GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 22/11/2019

Data, measures, designs and pictures are shown only as informativ purposes, and could be changed without previous notice