





Luminaire with MID power LED (double or single die) equipped with steel sheet heat sink / reflector pre painted in white colour. Body in PC grey RAL7035. Diffuser in PC U.V. ray stabilized. Sealing deposited by automatic machine. Fixing system for wall, ceiling or suspension with harmonic steel springs, and wide adjustable fixing range. Quick connector integrated in the fixture for wires with 12.5mm max. diameter. Electronic LED driver with power factor correction.

panoları	İç	Seri	SMART [3]
Tip	Tek başına	IP derecesi	IP66/IP69
Direnç dayanıklı	IK08	Yalıtım sınıfı	II
Akkor Tel Deneyi:	850 °C	uzunluğu	1200 mm
Yüzey sıcaklığı azaltılmış cihaz	Uyumlu	Ekran tipi	Opal
Çalıştırma sıcaklığı	-30 +50 °C	Ağırlık (kg)	2
Voltaj	220/240 V - 50/60 Hz - tek başına	Lamba	LED
Sürücü tipi	Constant Current Driver Led	Sistem gücü	20 W
Işık kaynağı tipi	LED - değiştirilemez	Renk sıcaklığı	4000 K (CRI>80)
Entegre LED'lerin etkinlik sınıfı	A + A++	Nominal flux (lm)	2900
Lümen çıkışı (lm)	2300	LED Life Time (L80B50)	100000 h
LED Life Time (L90B50)	50000 h	LED LifeTime (L80B20)	85000 h
Failure rate apparecchio (35.000h, Tq=35° C)	<2.5%	Failure rate apparecchio (50.000h, Tq=25° C)	<2.5%
Garanti	5 yıl	Overvoltage resistance	Common mode: 2KV; Differential mode: 1KV
Elektrokod	2434		

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



IP
IP66/IP69

IK
IK08



GWT
850 °C



CONSTANT
CURRENT
DRIVER



STANDARDS/APPROVALS



Data, measures, designs and pictures are shown only as informativ purposes, and could be changed without previous notice - Last update 23/10/2019