





Floodlight in die cast aluminum with galvanized bracket and painted the same color as the body. Equipped with graduate scale to facilitate orientation. Separated optical and electrical compartment. Front opening through manual hooks. Flat tempered glass 5mm thickness. Anti-aging silicone gasket. Power input through cable camp for cables $\varnothing 7 \div 10.5$ mm. Optic in 99.85% polished and anodised aluminium. Electrical componentent plate in galvanized steel. Tripolar terminal block. Wired version with power factor correction.

panoları	Dış	IP derecesi	IP66
Direnç dayanıklı	IK10	Yalıtım sınıfı	I
Rüzgara maruz maksimum yüzey	0.15 m ²	Aydınlatılan nesneden minimum uzaklık	1 m
Ağırlık (kg)	10.8	Renk	Grafit grisi
Voltaj	230 V - 50 Hz	Lamba gücü	250 W
Lamba akımı	3 A	Lamba tutucu	E40
lamba içinde	ST	Lamba dahil	Evet
Mevcut lambanın etkinlik sınıfı	A+	Uyumlu lambaların etkinlik sınıfı	A+ ÷ A++
Optik	Asimetrik - ULOR: 0%	Elektrokod	244B

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



IP

IP66

IK

IK10



0.15 m²



1 m



STANDARDS/APPROVALS



Data, measures, designs and pictures are shown only as informativ purposes, and could be changed without previous notice - Last update 20/11/2019